


# Vaportight LED Strip

## DIMENSIONS



## APPLICATION

The LVTS series is a next generation LED Vapor Tight fixture that provides maximum light output with durable construction. It is ideal for, featuring a one piece polycarbonate housing and lens. The LVTS was designed to meet or exceed IES recommended footcandle levels at installed heights for parking garages. Ideal for utility lighting, parking garages and stairwells; where meeting applicable building and safety codes is required.

## FEATURES

- High-transmission Frosted Polycarbonate Lens
- Direct replacement for fluorescent
- DesignLights Consortium Qualified luminaire
- Full distribution LED Luminaire
- Direct replacement of fluorescent
- Stainless Steel Latches are standard
- Long life, 60,000 hour LEDs at L80 reduce lift cycle maintenance costs

## ORDERING INFORMATION [\*Options in **Bold** denote Quick Ship configurations]

LVTS				
SERIES	WATTAGE	VOLTAGE	COLOR TEMPERATURE	OPTIONS
	48" Housing 34- 34W (3520 Lumens) 52- 52W (5200 Lumens)	<b>MV- 120-277V</b> MVD- 120-277V; 0-10V Dimming	840 - 80 CRI; 4000 Kelvin <b>850 - 80 CRI; 5000 Kelvin</b>	OS- 360 ° PIR OccupancySensor OSD- 360 ° PIR Occupancy Sensor w/ Daylight Sensor MOS- Integral Microwave Sensor FW3- 6; 3 Wire Fixture Whip FW4- 6; 4 Wire Fixture Whip EML8- Emergency Battery Pack, 800 Lumens EML14- Emergency Battery Pack, 1400 Lumens